

Parking Luminaire - Flog Maxi

VP.8XX.60.120.1500.365.2.N.K

The objective of our parking luminaire is to provide efficient and effective illumination for parking areas, ensuring enhanced visibility and safety. Designed with modern aesthetics, the luminaire seamlessly fits into various parking environments. Its energy-efficient features contribute to cost savings over time, and its durable construction ensures long-lasting performance.

L'objectif de notre luminaire de parking est de fournir une illumination efficace et performante pour les zones de stationnement, garantissant une visibilité et une sécurité accrues. Conçu avec une esthétique moderne, le luminaire s'intègre parfaitement dans divers environnements de stationnement. Ses caractéristiques écoénergétiques contribuent à des économies à long terme, et sa construction durable garantit des performances durables.



Specifications / Spécifications

Luminaire / Luminaire	
Product type / Type du produit	Parking Luminaire / Luminaire de Parking
Material / Matériel	ABS & PC / ABS et PC
Finish / Finition	Grey / Gris
Installation / Installation	
Environment / Environnement	Interior - Exterior / Intérieur - Extérieur
Type of Installation / Type d'installation	Ceiling mounted / Fixé au plafond
Mounting / Montage	Surface / Surface
IP / IP	65
Dimension / Dimension	1500x99x72 mm
Light source / Source de lumière	
Power / Puissance	60W (± 5%)
Lumen output / Flux lumineux	7800lm (± 5%)
CRI / IRC	80+
CCT / CCT (XX)	3000K (30) - 4000K (40) 6000K (60)
Optics / Optique	
Emission / Émission	Direct / Directe
Beam Angle / Angle de faisceau	120°
Type / Type	Fixed
Electrical equipment / Équipement électrique	
Main voltage / Tension principale	220-240 V
Frequency / Fréquence	50-60 Hz
Dimming type / Type de gradation (N)	ON/OFF (1) - DALI (2)
Optional Accessories / Accessoires Optionnels	
Optional Kit / Kit Optionnel (K)	None / aucun () Emergency Kit 3h / Kit d'Urgence 3h (E)

