

Uplight Wall Washer - Linari

UR.8XX.42.BB.1000.166.2.N

Designed for flexible architectural lighting, this wall washer is available in 42W outputs. With multiple beam angles, colour options, and dimmable functionality, it ensures tailored illumination. Adjustable brackets provide easy installation and precise light direction, making it suitable for a range of interior applications.

Conçu pour un éclairage architectural flexible, ce wall washer est disponible en versions 42W Avec plusieurs angles de faisceau, options de couleur et une fonction dimmable, il garantit un éclairage sur mesure. Des supports réglables assurent une installation facile et une orientation précise de la lumière, le rendant adapté à une large gamme d'applications intérieures.



Specifications / Spécifications

Luminaire / Luminaire	
Product type / Type du produit	LINEAR WALL WASHER / Applique murale linéaire
Material / Matériel	Aluminium/ Aluminium
Finish / Finition	Black/ Noir

Installation / Installation	
Environment / Environnement	Exterior / Extérieur
Type of Installation / Type d'installation	Celing, Floor mounted / Monté au plafond, sol
Mounting / Montage	Surface / Surface
IP / IP	66
Dimension / Dimension	Length: 1002 mm

Light source / Source de lumière	
Power / Puissance	42W (± 5%)
Lumen output / Flux lumineux	3920lm (± 5%)
CRI / IRC	80+
CCT / CCT (XX)	2700K (27) - 3000K (30) 4000K (40) - 6000K (60)

Optics / Optique	
Emission / Émission	Direct / Directe
Beam Angle / Angle de faisceau (BB)	15° (15) - 30° (30) - 45° (45) - 60° (60)
Type / Type	Adjustable Bracket

Electrical equipment / Équipement électrique	
Main voltage / Tension principale	100-240V AC
Frequency / Fréquence	50-60 Hz
Dimming type / Type de gradation (N)	ON/OFF (1) - DALI (2)

Accessories/ Accessoires	
Accessories/ Accessoires	YES / OUI Adjustable brackets/ Supports réglables

